



SX blade

### Standard version

The 27SX and 33SX series come as standard with a quick-change system for the spade blades (SX).

For safety purposes, each machine has a torque limiter on the Walterscheid PTO. This special PTO ensures that the drive stops if there is an obstacle in the machine.

The 27SX series is suitable for tractors from 35 to 70 hp. Working widths from 120 to 180 cm are possible.

The 33SX series is suitable for tractors from 60 to 90 hp. This series has a choice of working widths: 210 cm or 250 cm.

Model	Working width	Working depth	Number spades	Ideal speed	Required horse-power	Maximum horse-power	Weight
27SX120R	120 cm	15-30 cm	12	1 - 3.5 km/h	35 hp	70 hp	460 Kg
27SX120RH	120 cm	15-30 cm	12	1 - 3.5 km/h	35 hp	70 hp	615 Kg
27SX150R	150 cm	15-30 cm	16	1 - 3.5 km/h	40 hp	70 hp	530 Kg
27SX150RH	150 cm	15-30 cm	16	1 - 3.5 km/h	40 hp	70 hp	685 Kg
27SX160R	160 cm	15-30 cm	16	1 - 3.5 km/h	40 hp	70 hp	560 Kg
27SX160RH	160 cm	15-30 cm	16	1 - 3.5 km/h	40 hp	70 hp	700 Kg
27SX180R	180 cm	15-30 cm	16	1 - 3.5 km/h	48 hp	70hp	580 Kg
27SX180RH	180 cm	15-30 cm	16	1 - 3.5 km/h	48 hp	70 hp	730 Kg
33SX210K	210 cm	15-30 cm	20	1 - 3.5 km/h	70 hp	90 hp	800 Kg
33SX210KH	210 cm	15-30 cm	20	1 - 3.5 km/h	70 hp	90 hp	1000 Kg
33SX250K	250 cm	15-30 cm	24	1 - 3.5 km/h	75 hp	90 hp	880 Kg
33SX250KH	250 cm	15-30 cm	24	1 - 3.5 km/h	75 Pk	90 Pk	1100 Kg

The machines with an H in the modelname are with the driven crumbler roller.

For more information please call Imants or consult our website [www.imants.com](http://www.imants.com).



**imants**  
125 Years Quality Cultivation

27SX and 33SX SERIES



Imants bv  
Postbus 2  
5540 AA Reusel  
The Netherlands

T: +31(0)497 64 24 33  
F: +31(0)497 64 32 05  
E: [info@imants.nl](mailto:info@imants.nl)

Dealer:

[www.imants.com](http://www.imants.com)

Good mixing effect Intensive tilling Minimal maintenance Large capacity  
Better incorporation of organic material Better water management Intensive tilling Less fuel  
Unique spade shaft 1-process seed bed Faster warming of seed bed No plough pan



## 27SX and 33SX SERIES

**imants**  
125 Years Quality Cultivation


Spading machines for sandy/loamy soils. The 27SX and 33SX series are compact and uncomplicated spading machines used in many industries. The machines can be fitted with a crumbler roller. So the primary tillage (spading) and secondary tillage (seedbed preparation) can be done in one pass.

### Machine design

The new “flat” design and the distinctive yellow stripes combined with Imants blue and black give the machines a unique appearance.

The spader works the soil by means of the spade shaft. On this shaft there are rows, each with a number of spade arms, the number of rows and spade arms depending on the machine and the working width.

What is unique about these spade arms is the kink to the left and right. This means there are fewer banks and therefore more “room” in the machine. There is less chance of clogging, the machine can be operated at higher speed, and the soil is tilled perfectly.



The crumbler roller is fitted directly behind the spade shaft. The crumbler roller is a driven tube with hardened spring tines mounted on it. Its special design makes the crumbler roller suitable for:

- a perfectly consolidated seed bed
- a levelling effect
- the incorporation of organic matter

Types 27SX and 33SX are driven by a PTO shaft (540 rpm) and are carried by the three-point hitch. The machine lowers by means of the hitch until the crumbler roller supports a large part of the machine. The working depth is then adjusted using the position adjuster on the tractor.

On one side there is a spade shaft drive and on the other the crumbler roller drive.

### Spading - general

Because of upscaling and the continual increase in fuel prices, it is important to choose a machine with high capacity and low fuel consumption. Imants combines these factors in its spaders so the soil can be worked in an attractive and smooth manner.

During spading, organic matter is mixed through the most biologically active, oxygenated topsoil. Stubble, residue, stable manure, compost and green manure can easily be incorporated in a single process.

This means the organic matter becomes available immediately as food for micro-organisms.

There is no plough pan because of the unique way the spades are inserted. The result is better water management, while fertilisers and minerals are better used.

Because the spade shaft pushes “forwards”, less tractive force is needed compared to ploughing. Another feature is that the tractor rides on the topsoil and not in the furrow, so there is no compression of the deeper soil layers. The spading machine removes all compressed soil up to spade depth to create the perfect seed bed without clumping. And the fuel consumption per hectare is lower!

### Potential applications

The 27SX and 33SX series are ideal for sandy and loamy clay soils throughout the world.

The machines have a working depth of 15 to 30 cm and till the soil evenly over the entire working depth and width.

Thanks to its simple design and compact size, the machine is ideal for small to medium horticulture, arable farming, green space and gardening companies. Tree nurseries and greenhouses as well!

The spading machine is also made for smaller plots

and strip cultivation. The ends are worked as efficiently as the sections in the middle. There is no furrow!

### Advantages at a glance:

- Good mixing effect
- Better incorporation of organic material
- Less fuel
- Minimal maintenance
- Intensive tilling
- Better water management
- Less compaction
- Large capacity
- Better soil structure
- 1-process seed bed
- Perfectly seed bed with crumbler roller
- No plough pan
- Unique spade shaft
- Faster warming of seed bed

